

List of Standard Products

Ionic water valves



The proper way to select **ionic water valve** is by the size of the diameter of pipe where it wants to be installed. The more magnets, the better performance. In some case it might be needed more than one **ionic water valve** to get the proper results. **ionic water valve** with less magnets, we recommend it only for circular system. We also do not recommend to upgrade the size of the diameter with the original size of the pipe.

Applications	Model	Magnets	Diameter	Descriptions	
New Facilities	Circulation System	TA-15M2	Rc1/2 (15A)	主に工業用の循環回路に使用 Select by the size of the pipe's diameter. These products has 2 magnets therefore we recommend them for a circular system.	
		TA-20M2	Rc3/4 (20A)		
		TA-25M2	Rc1 (25A)		
		TA-32M2	Rc1-1/4 (32A)		
		TA-40M4	Rc1-1/2 (40A)		
		TA-50M4	Rc2 (50A)		
	Existing Facilities	Circulation System	TA-15M4	Rc1/2 (15A)	主にワンパス又は循環回路に使用 Select by the size of the pipe's diameter. These products has 4 magnets therefore we recommend them for direct pass (new pipe) or circular system. Even though the pipes are new and if the water's quality is poor, then we recommend ion water valves with 6 to 12 magnets.
			TA-20M4	Rc3/4 (20A)	
			TA-25M4	Rc1 (25A)	
		TA-32M4	Rc1-1/4 (32A)		
		TA-40M8	Rc1-1/2 (40A)		
		TA-50M8	Rc2 (50A)		
Special Products	Circulation System	TA-15M6	Rc1/2 (15A)	主にワンパス又は循環回路に使用 One pass it's recommend to use the products with 6 magnets rather than 4 magnets or 12 magnets rather than 8 magnets.	
		TA-20M6	Rc3/4 (20A)		
		TA-25M6	Rc1 (25A)		
		TA-32M6	Rc1-1/4 (32A)		
		TA-40M12	Rc1-1/2 (40A)		
		TA-50M12	Rc2 (50A)		
	TA-65M12	Flange 65A	大口径用フランジ式 The flange types are used example: In building or factories where the pipe's diameter are large.		
	TA-80M12	Flange 80A			
	TA-100M16	Flange 100A			
	TA-125M20	Flange 125A			
IWV-15M12	12pc	Rc1/2 (15A)	Cooling tower in plant: A short distance circulation. Housing: Water branch area for a header method.		
IWV-20M12	12pc	Rc3/4 (20A)			
Special Products	IW6 series	2pc	R3/8xRc1/8-3/8	These products mainly to be used at the inlet of the temperature controllers for circular system. 工業用の循環系に使用	
	IW8 series		R3/8xRc1/8-3/8		
	IWV-15M4	4pc	Rc1/2 (15A)		
	IWV-20M4		Rc3/4 (20A)		
	BP-8	6pc	Rc1/4 (8A)		ボイラーの燃費改善に有効 Boiler fuel saver product "BP series" BP gives good effect to fuel oil (lubricating oil/gasoline/kerosene/light oil/heavy oil). Boiler fuel economy less emission.
	BP-10		Rc3/8 (10A)		
	BP-15	12pc	Rc1/2xR1/2(15A)		
BP-20	Rc3/4xR3/4(20A)				

